



Engine Driven Portable High Pressure Pumps

Die-Cast Aluminum or Cast Iron, Self-Priming Engine Driven Pumps with B&S or Honda gasoline or Yanmar diesel Engines. Provides Home Fire Protection with optional Hose Kit

- **Horsepower 5.5 to 6.5**
- **2" Suction and Discharge Port Sizes**
- **Die-Cast Aluminum or Cast Iron**
- **Max. Flow: 120 GPM**
- **Max. Head: 88 PSI**
- **Max. Lift: 18 ft.**
- **Silicon Carbide Seal with Dry Run Survivability**
- **Use for Fire Protection or Irrigation**
- **Optional High Pressure Hose Kit**
- **Optional Viton® Elastomers**
- **Optional Wheel Kit**




High Pressure Hose Kit 55-338


These Pumps are capable of developing 75 lbs. of pressure at 30 GPM: use for fire protection or irrigation. Available with a wide choice of standard and heavy-duty engines for gasoline and diesel fuels. Unit is standard with die-cast aluminum housing and impeller or Cast-Iron, G-Ruff Coat Teflon® housing with bronze impeller. All models standard with EPDM elastomers, Viton® fitted silicon-carbide self-lubricated seal. All models (except Honda and Yanmar powered models) carry "Made in U.S.A." labeling.

*Viton® and Teflon® are registered trademarks of DuPont

COMMERCIAL DUTY




Model 2P5IR



Model 2P5ICR

Performance of High Pressure Pumps



Portable- High Pressure Pumps

2" Gen Purpose-High Pressure Pumps

Alum. Model #	Alum. Ship Wt. (lbs.)	Cast Iron Model #	Cast Iron Ship Wt. (lbs.)	Driver Type & HP	Seal Type & Elastomer/Faces	Tank Size (Qts.)	Run Time	Mounting
2P5A	64			B&S 5.5 hp OHV	Viton®*/Sic/Sic	3	1.4	Handle
2P5AR	78	2P5ACR	100	B&S 5.5 hp OHV	Viton®*/Sic/Sic	3	1.4	Roll Cage
2P5IR	86	2P5ICR	108	B&S 6.5 hp Pro	Viton®*/Sic/Sic	4	2	Roll Cage
2P5HR	82	2P5HCR	104	Honda 5.5 hp	Viton®*/Sic/Sic	3.88	2	Roll Cage
2P5YR	103	2P5YCR	125	Yanmar 4.7 hp	Viton®*/Sic/Sic	2.6	1.8	Roll Cage

5/8 Threaded Kit (Single)

Alum. Model #	Alum. Ship Wt. (lbs.)	Cast Iron Model #	Cast Iron Ship Wt. (lbs.)	Seal Type & Elastomer /Faces	Mounting
2P5	31	2P5C	31	Viton®*/Sic/Sic	Handle

2" High Pressure Hose Kit

Model #	Ship Wt. (lbs.)
55-338 (100 ft.)	38
55-374 (50 ft.)	38

*Viton® and Teflon® are registered trademarks of DuPont

Standard Features



- Aluminum Closed Impeller and Cast Iron Volutes- Die Cast Pump
- Bronze Closed Impeller and Cast Iron Volute- Cast Iron Pump with G-Ruff Coat Teflon®*.
- Built-In Carrying Handle
- Large Pump Casing
- Built-In Check Valve
- Horizontal Discharge and Male Threaded Connections
- Silicon Carbide, Self-Lubricated Seal with Graphite Impregnated Seat and Viton® Elastomers
- Choice of Briggs & Stratton Standard or Premium, Honda gas or Yanmar diesel Engines
- Optional Wheel Kit
- Strainer Supplied
- Rubber Foot Mounting

WARNING: Do not use in explosive atmosphere or for pumping volatile flammable liquids.

Viton® Elastomers including O-rings and check valve.

Hose Kit with 50 ft. or 100 ft. of high pressure discharge hose, 15 ft. of suction hose, fire nozzle, hose wrench and adapter.

Two wheel truck assemblies with semi-pneumatic tires for pumps with roll cages.



DIMENSIONS:

INCHES

[MILLIMETERS]

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	DISCH*	SUCT*
2P5	18.50 [469,9]	17.00 [431,8]	12.81 [325,4]	7.38 [187,4]	2.83 [71,9]	10.29 [261,4]	5.00 [127,0]	15.00 [381,0]	25.00 [635,0]	16.62 [422,1]	11.36 [288,5]	1.62 [41,1]	* 2.00	* 2.00

(*) STANDARD NPT (MALE) PIPE THREAD.

HIGH PRESSURE PUMP