

## Hand Oscillating Drum Pump

- Self Priming
- Compact
- Cast Iron construction with Buna-N seal and bronze valves
- ► Delivers 6 GPM, .10 of a Gallon per stroke
- Suction and discharge tube included

Cast iron hand oscillating pump is a high quality unit designed for the transfer of and dispensing of lubricating oils and other non-corrosive liquids which are compatible with pump component materials. Pumps will have suction lift of 15 feet. Provides accurate measurement of fluids and will provide up to 50 PSI for prelube applications.



Catalog Number Stock No.	Description/ Type of Pump	Ship Wt (Lbs)	Driver Type	Port size Suc x dis (NPT)	Basic Construction	Seal Type & Elastomer/ Faces
H03/4A4-36DK	3/4" Hand Oscillating Drum Pump	13	Manual	3/4 X 3/4	Cast Iron	Buna-N Lipseal

## **Standard Features**

- ➤ Cast Iron Construction
- ➤ Buna-N Seal, Bronze Valves and Fiber Gasketing
- ➤ Maximum Temperature 120° F
- ➤ Maximum Pressure 50 PSI.
- ➤ 6 GPM @ 60 Strokes per Minute
- ➤ 3/4" Suction Tube and Discharge Spout
- > 2" Bung Adaptor
- ➤ Ship Wt. 13 lbs.

